

# Effect of Early-Age Concrete Elastic Properties on Fatigue Damage in PCC Pavements With & Without Fibers

Mohsen Issa, Ph.D, PE, SE, FASCE, FACI  
Department of Civil and Material Engineering  
University of Illinois at Chicago

Presented By James Krstulovich, PE  
Bureau of Materials  
Illinois Department of Transportation

**CIVIL  
AND MATERIALS  
ENGINEERING  
COLLEGE OF  
ENGINEERING**

**UIC**



**ILLINOIS CENTER FOR  
TRANSPORTATION**



**Illinois Department  
of Transportation**

# The Research Objective

---

- **Technically:** To investigate how early-age elastic properties in concrete pavements might resist damage due to early loading fatigue, particularly as it impacts long-term durability.
- **Basically:** Can ordinary PCC pavements or patches be opened earlier than currently specified? Does including fibers help?
- **Why?** May result in decreased time for opening to traffic: potential cost savings through use of shorter periods of traffic control, as well as potential for enhancing highway user satisfaction.

# Our Inspiration

---

- A 20+ yr-old pavement showing no damage associated with it having been driven on when it was 'green' enough to leave tire impressions.



**Obviously we do not want to open this early,  
but is there a time between this and when the concrete achieves 3500 psi compressive?**

# Primary Research Tasks

---

- Literature Review
- **Stage 1:** Laboratory Characterization of Mixes
  - Conventional paving and patching concrete with & without structural synthetic fibers
- **Stage 2:** Parametric Finite Element Analysis
- **Stage 3:** Laboratory Study of Jointed Slab Sections
- Final Report (September/October 2017)

# Stage 1 Testing Highlights: Nominal Mix Designs

Mixture	Cementitious, pcy	w/cm	Slump, in.	Air, %	Fiber*, pcy
PV	565	0.42	2 - 4	5.0 - 8.0	--
PV-Fiber	565	0.42	2 - 4	5.0 - 8.0	4, 6, & 8
PP-1	650	0.42 - 0.44	2 - 4	4.0 - 7.0	--
PP-1-Fiber	650	0.42 - 0.44	2 - 4	4.0 - 7.0	4
PP-2	735	0.36	2 - 6	4.0 - 6.0	--
PP-2-Fiber	735	0.36	2 - 6	4.0 - 6.0	4

\*Two different brands of synthetic fibers were investigated

- Type I Portland Cement
- Grade 100 Slag Cement @ 25% replacement
- Natural Sand
- 3/4" Crushed Limestone

# Stage 1 Testing Highlights:

## Mix Characterization

---

### Mechanical Properties

- Compressive Strength
- Flexural Strength (Modulus of Rupture, MOR)
- Flexural Toughness ( $T_{150}^D$ )
- Static Elastic Modulus ( $E_s$ )
- Relative Dynamic Modulus ( $E_D$ )


All tests performed at the following ages:

- 12, 24, & 72 hrs and
- 7, 14, & 28 days

# Stage 1 Testing Highlights: Mix Characterization Cont'd

## ● Fracture Mechanics

- 3x4x16-in. notched prism
- Followed RILEM (Jenq & Shah, 1985) to calculate Critical Stress Intensity Factor ( $K_{IC}$ ) and Critical Crack Mouth Opening Displacement ( $CMOD_C$ )
- For each test, 2 cylinders were tested for RDM and compressive strength



# Stage 1 Testing Highlights: Fatigue Testing

## ○ Flexural Fatigue Testing

- Developed S-N curves for 6x6x21-in. beams tested at 12, 24, & 72 hrs, and 7 days of age
- Range of applied stresses was determined based on MOR of the mix at each age
  - $\sigma_{i\_max} = S_i \times MOR$
  - $\sigma_{i\_min} = 0.1 \times \sigma_{i\_max}$
- Stress Levels ( $S_i$ ) were set to 0.9, 0.8, 0.7, & 0.6





# Stage 1 Testing Highlights:

## Fatigue Testing

---

### Accounting for early-age strength gain



- As the concrete gains strength, the stress level will decrease.
- Thus, it was necessary to increase amplitude and mean load with time to maintain a constant stress level during testing.

# Stage 1 Testing Highlights:

## Fatigue Testing – Early Strength Gain

A logarithmic function (normalized with respect to MOR @ 12 hrs) was developed to predict the strength gain over 48 hrs:

$$f'_r(t)/f'_{r\ 12\ hrs.} = \begin{cases} \frac{-733 + 374 \text{ Log}(t)}{196} & \text{for } 12 \text{ hrs} \leq t \leq 24 \text{ hrs} \\ 2.32 \times \frac{-302 + 225 \text{ Log}(t)}{413} & \text{for } 24 \text{ hrs} < t \leq 48 \text{ hrs} \end{cases}$$




# Stage 1 Testing Highlights:

## Fatigue Testing & Durability

---

- **Next step:** Can we subject a specimen to fatigue and then assess its long-term durability?
- **What did we try?**
  - First, subject specimen to fatigue cycling at early ages: 12 hrs, 24 hrs, 72 hrs, & 7 days
  - Then, subject specimen to freeze/thaw (ASTM C 666, Procedure A)
  - Assess damage in terms of RDM


# Stage 1 Testing Highlights: Fatigue Testing & Durability



# Stage 2

## Analysis and Modeling

- Finite Element Analysis was used to correlate the physical and fatigue testing results to pavement response
- Parametric modeling was used to identify the stress level generated at critical positions due to ESAL loadings,
- For example: Cross-Traffic
  - Critical case for truck loading a slab transversely
  - Higher axle loading, higher tire contact pressure
  - Looking for cases of flexural failure, shear failure, faulting, or corner breaks



# Stage 2 Analysis and Modeling: Design Parameters

- Pavement Thickness: 6, 8, 10, 12, 14, and 16 in.
- Modulus of Subgrade Reaction: 50, 100, 200, 300, and 500 psi/in.
- MOE estimated empirically based on test results obtained during mix characterization

Age	12 Hours	1 Day	3 Days	7 Days
$f'_c$ (psi)	1312.3	2440	3692.5	4836
MOE (psi)	1.767E+06	2.518E+06	3.190E+06	3.722E+06

# Stage 2 Analysis and Modeling: Design Parameters Cont'd


Model parameters	Slab dimensions	12 x 15 ft.
	Number of lanes	2
	Number of slabs per lane	3
	Subgrade Model type	Winkler model
	Mesh size	2 x 2 in <sup>2</sup>
Concrete parameters	Unit weight	144 lbs./ft <sup>3</sup>
	Poisson's ratio	0.15
Vehicle Load parameters	Axle type	Single Axle/Single Tire
	Aspect ratio of contact area	1
	Axle Span (c-c of contact area)	6 ft.
	Axle position (from bottom left)	134 in, 229.2 in.
	<b>Axle load</b>	<b>22,000 lbs.</b>
	Contact area of tires	200 in <sup>2</sup>
	<b>Tire Pressure</b>	<b>110 psi</b>
Joint parameters	<b>LTE</b>	<b>90%</b>

# Modeling Results

## Cross-Traffic Construction Traffic

Out of 120 cases

- Possible flexural failure when opening at:
  - 12 hrs: 16 cases when  $t \leq 12''$
  - 24 hrs: 7 cases when  $t \leq 8''$
  - 72 hrs: 1 case when  $t = 6''$
  - 7 days: none






# Modeling Results

## Cross-Traffic Construction Traffic

- Possible shear failure when opening at:
  - 12 hrs: 11 cases when  $t \leq 10''$
  - 24 hrs: 7 cases when  $t \leq 8''$
  - 72 hrs: 5 cases when  $t = 6''$
  - 7 days: 4 cases when  $t = 6''$
- Majority of these 'failing' cases were for a combination of variables probably unlikely to occur in the field (e.g., very low modulus of subgrade reaction).




# Stage 3 Laboratory Study of JPCP Slabs: Currently In Progress

---

- **What?** Subjecting early-age fatigue loading to experimental-scale jointed slabs
  - Thicknesses: 6 & 8 in.
  - With & without fibers (4 & 8 pcy)
  - With & without dowels (1 & 1-1/4 in.)
- **Why?** Complements the physical testing and analytical modeling already conducted
  - Also, provides information regarding joint effects: shear, bending, flexural stresses, dowel bar effects

# Stage 3 Laboratory Study of JPCP Slabs: Experimental Setup

Top View



Side View

# Stage 3 Laboratory Study of JPCP Slabs: Loading Parameters

---

- Start with static loading to **9 kips** ( $\frac{1}{2}$  ESAL)
  - Rate of loading **0.02 in/min**
- Measure initial **Load Transfer Efficiency** and **Joint Effectiveness (E)**
- Commence **cyclic fatigue** at 4 Hz
  - Max. applied load: **9 kips**
  - Min. load: 0.1 (Max)
- Measure LTE and E @ **10,000; 100,000; 300,000; 700,000; and 1,000,000** cycles
  - **LTE > 60 % or E > 75%** are considered adequate after **1 million cycles** as recommended by ACPA

# Stage 3 Laboratory Study of JPCP Slabs: 1<sup>st</sup> Slab Tested

---

- Max. applied load: **9 kips** (initially)
- No. of cyclic loads: **1 million** cycles, then extended to **2.3 million**
- **LTE** and **E** values: **100%**
- Overall deflection: **0.462 in.**
- **Contraction joint crack initiation** started at bottom of slab after 250,000 cycles
- Max. applied load was then increased by 50% to **13.5 kips for 1 million more cycles**
  - **LTE** and **E** remained at **100%**
  - Overall deflection: **0.503 in.**
  - No further crack initiation or propagation

# What's Next?

## Currently In Progress

---


- Developing a **practical procedure** for determining time to opening based on fatigue testing results, MOR/Dynamic Modulus, and Finite Element Analysis
- **What is this looking like so far?**
  - **Nomographs** correlating subgrade modulus, pavement thickness, and max. stress
  - **Fatigue Life formulae** developed for concrete ages: 12, 24, & 72 hrs, and 7 days

# Draft Procedure for Early Opening

## Example of Nomograph

- Concrete @ 24 hrs
- Modulus of Subgrade Reaction,  $k$  (psi/in)
- Pavement Thickness (in.)

Estimates maximum tensile stress to develop at the bottom of the slab under 1 ESAL



# Draft Procedure for Early Opening

## Example of Fatigue Life Formula

---

### Concrete @ 24 hrs

- $S_{24} = \frac{\sigma_{max}}{MOR_{24}}$

- $N_{24} = e^{-\left(\frac{S_{24}-1.0066}{0.025}\right)}$

- *Fatigue Life* =  $\frac{N_{24}}{4 \text{ Hz}}$

- Where:  $\sigma_{max}$  = Max. tensile stress developed due to 1 ESAL (from nomograph)

$MOR_{24}$  = Modulus of Rupture at 24 hrs\*

$S_{24}$  = Stress level at 24 hrs

$N_{24}$  = No. of cycles until failure

\* Can be measured or estimated from correlation to Dynamic Modulus



---

Question?