



SHOTCRETE SPECIFICATIONS



An Introduction to the Shotcrete Process

american
shotcrete
association

ASCA

American Shotcrete Association

The American Shotcrete Association is a non-profit organization of contractors, manufacturers, engineers, owners, and others with a common interest in promoting the use of shotcrete. Formed in March, 1998, the first Board of Directors was elected in October of that year.

The **Vision** of the American Shotcrete Association is *"that the shotcrete process be understood and used in every beneficial application"*.

The **Mission** of the ASA is *"to encourage and promote the safe and beneficial use of the shotcrete process"*.

Seminar Content

- Definition of Shotcrete
- Shotcrete Processes
- Shotcrete Applications
- The Shotcrete Specification
 - *Environmental conditions*
 - *Surface Preparation*
 - *Reinforcement*
 - *Shotcrete Mix Components*
 - *Quality Assurance*
 - *Shotcrete Application*
 - *Finishing and Curing*
 - *ACI Nozzleman Certification*
- Useful Tools and Resources

Shotcrete - Definition



“Concrete placed by a high velocity pneumatic projection from a nozzle.”

As defined in ACI CT-13 *Concrete Terminology*

Shotcrete is not a product...




...It is simply a method of placing concrete

History of Shotcrete



Carl Akeley
Original Shotcrete Gun
1907

Dry-Mix Shotcrete
1920's




History of Shotcrete



Dual chamber
Shotcrete gun 1922

Dry-mix shotcrete
1922



History of Shotcrete



Dry-mix shotcrete
Today



american
shotcrete
association

ASCA


Processes

Dry-mix shotcrete process


The dry concrete mixture is conveyed through a hose in an air stream at high velocity. Water is added at the nozzle to produce plastic material on impact. Mixing of water and the dry material occurs at the nozzle and on the receiving surface.



Dry-Mix Process



Dry-Mix Nozzle Cross Section



Dry Mix Nozzle tips help with the material mixing.

Removable tips increase the material velocity.

Tip lengths and shapes will change the material spray pattern.



Processes

Wet-mix shotcrete process

The concrete is pumped through a hose and air is added at the nozzle to accelerate the mixture to a high velocity.






Fig. 2.1 — Equipment layout: dry-mix versus wet-mix shotcrete.

Wet-Mix Process


Ready-Mix Truck




Concrete Mixer / Pump



Concrete Pump



Nozzleman




Reinforcing Steel



Air Compressor



Rebound





american
shotcrete
association

ASCA

Wet-Mix Shotcrete Nozzle

Nozzle Design for Wet Shotcrete Equipment





Dry vs Wet Process?

Specifications should be performance based and left to the choice of the contractor

Uses of Shotcrete

Structural rehabilitation

- Buildings, parking structures, historic



Uses of Shotcrete

Infrastructure rehabilitation

- Bridges, tunnels, underground etc.



Uses of Shotcrete

Infrastructure rehabilitation


- Dams and hydraulic structures (water reservoirs, canals, spillways, locks, creek stabilization, etc.)



Uses of Shotcrete

Infrastructure rehabilitation


- Marine structures (piers, wharves, sea walls, light stations, berth faces, dry docks, etc.)



Uses of Shotcrete

Infrastructure rehabilitation

- Strengthening and seismic retrofit



Tunnel Enlargement



american
shotcrete
association

ASCA

Underground Subway Stations



american
shotcrete
association

ASCA

Slope Stabilization

- Rock Slope Stabilization
- Earth Embankments
- Creek Channelization
- Containment Beams

Tunnel Portal



Soil Nailed Slope



Bridge Repair



Bridge Reconstruction



Zoo Exhibit – Simulated Rock



The Shotcrete Specification

The Key to a Successful
Project

Environmental Conditions

Cold weather – Follow ACI 306R (Cold Weather Concreting)

- Do not apply shotcrete if air temperature is 40°F (5°C) and falling unless protective measures taken
- Do not apply shotcrete on frozen surfaces
- Keep mix temperature above 50°F (10°C)
- Protect shotcrete from freezing until it has reached at least 500 psi (4 MPa) in compressive strength
- Use warm mix water

Environmental Conditions

Hot weather (Follow ACI 305R Hot Weather Concreting)

- Keep shotcrete mix temperature as low as possible
- Do not apply shotcrete when ambient temperature above 100°F (38°C) unless precautions taken
- Use cool water in mixture
- Use shades where possible
- Use fogging / misting for cooling and controlling evaporation

Environmental Conditions

Wind

- Do not apply shotcrete during high wind conditions
- Provide protective barriers
- Causes separation of fines in nozzle stream
- Causes high rates of evaporation
- Can cause plastic shrinkage cracking


Environmental Conditions

- Rain
 - Do not apply shotcrete if during heavy rain or if heavy rain is forecast
 - Do not apply shotcrete onto surfaces with ponded or running water
 - Use tarpaulins / tents to protect from rain




Preparation of Existing Structure

- Concrete Removal
- Saw cut the edge of the repair area at a minimum depth of $\frac{3}{4}$ " (20 mm)
- Avoid feather-edging!
- Remove any loose or unsound concrete
- Maintain a minimum clearance of 1" (25 mm) behind exposed reinforcing steel.



Preparation of Existing Structure

- Immediately before shotcrete application:
- Pressure wash concrete surface
- Ensure all loose debris, dust etc is removed
- Bring surface to saturated, surface dry condition (SSD)



Preparation of Existing Structure

- Bonding agents are **never** recommended for wet or dry mix shotcrete applications
- The nature of the shotcrete process ensures excellent bond to properly prepared SSD substrate
- Bonding agents **will** create a “bond breaker” at the interface between the shotcrete and the substrate and **will** lead to bond failure

Formwork

- One-sided forms may be used to provide gunning surface
- Ensure formwork is stable and properly braced
- Apply form release agents to strippable formwork
- Ensure formwork is clean and free of debris (overspray/rebound)

Reinforcement

- Ensure that bars are properly anchored to prevent movement or vibration during shooting
- Wire mesh may be used to minimize cracking due to drying shrinkage



Alignment Control

- Use alignment control devices to establish line and grade. Devices include:
 - *Ground wires (piano wire)*
 - *Pencil rods (1/4" high tension pre-stressing steel) for curved profiles*
 - *Depth gages*
 - *Guide strips/formwork*



Alignment Control




Figure 2: Ground wire delineates finish of a corner without restriction of nozzle trajectory.




Figure 3: Small diameter steel rod delineates final curvature contour of a bridge pier.

Pencil
Rods

Typical Shotcrete Mixture


- Cement (Type I II or III) 17 - 20%
- Silica Fume 1.5 - 8%
- Water Reducing Admixtures Wet mix only
- Blended Aggregates 75 – 80% (ACI
Gradation No.
1 or 2)
- Air-entraining admixture*
maximum
spacing factor of 300 μm
To provide
- Synthetic Fibers* 1.7-3.4 lbs/yd³
- Steel Fibers* 65-115 lbs/yd³
- *Project specific

Cementing Materials

- Cement should be type I, II or III and should conform to ASTM C 150
- Cement will vary by geographical region and will affect properties such as set time and water demand.
- Water/Cementitious material ratio should range between 0.30 to 0.45.

Silica Fume

- Silica fume is a byproduct of producing silicon metal or ferrosilicon alloys.
- Round particle (100-200x smaller than Portland cement)
- High SiO_2 content



Silica Fume



Benefits of Silica Fume Plastic Properties

- Improves adhesion
- Increases cohesive properties of shotcrete mixes
- Improves build up before sloughing
- Reduces rebound
- Improves wash-out resistance



Benefits of Silica Fume

Hardened Properties

- Provides higher compressive & flexural strengths
- Reduces porosity (permeability) - Improves durability
- Improves resistance against alkali aggregate reactivity
- Improves resistance to sulfate & chemical attack
- Reduces chloride ion penetration - Reduces corrosion of embedded reinforcing steel

Benefits of Fly Ash Plastic Properties

- Easier to pump
- Slower reaction and set time –
 - good in hot weather
 - Not in cold weather

Benefits of Fly Ash

Hardened Properties


- Reduces porosity (permeability) - Improves durability
- Improves resistance against alkali silica reactivity (ASR)
- Improves resistance to sulfate & chemical attack
- Higher long-term compressive strength

Set Accelerators

- Improve ability to build thicker applications in a single pass (in wet areas, increases productivity)
- Reduces set time and develops higher, early age compressive strength (Open areas to traffic quicker – bridges, parking decks, subways)
- Accelerator **MUST** be added using controlled dosing methods. Too much accelerator is detrimental to quality of the concrete!

Air Entraining Admixtures


Dry-Mix Shotcrete



Air Entrained



Non-Air Entrained





Air-entrained (300 cycles)



Not Air-Entrained (300 cycles)

Synthetic Fibers

■ Micro Fiber

- *Dosage rate of 1 to 3 lbs/yd³ (0.6-1.8 kg/m³) as recommended by manufacturer*
- *May be added to reduce the possibility of early-age shrinkage cracking (plastic shrinkage)*

■ Macro Fiber

- *Dosage rate of 3 to 12 lbs/yd³ (1.8-7.2 kg/m³)*
- *May be added to reduce the possibility of shrinkage cracking (plastic shrinkage)*
- *May be added to increase toughness and energy absorption*

Steel Fibers

■ Steel Fiber

- *Dosage rate of 60-100 lbs/yd³ (40-60 kg/m³) as recommended by manufacturer*
- *Should not be used in conjunction with wire mesh*
- *May be added to reduce the possibility of shrinkage cracking*
- *May be added to increase toughness and energy absorption*

Aggregates

ASTM C 33

All normal weight aggregates used in shotcrete mix designs should comply with ASTM C 33


ACI Gradations

The combined aggregates should meet one of the following gradations specified by ACI.

- Gradation No. 1 - Fine aggregate shotcrete
1/4" maximum aggregate size
- Gradation No. 2 - Fine and coarse aggregate
3/8" maximum aggregate size

Aggregates

ACI 506R – Guide to Shotcrete - Gradation No. 1 and 2



Fiber Reinforcement

- Monofilament Micro-Synthetic Fibers – Typically used in repair applications to minimize cracking due to drying shrinkage
- Steel Fibers - Typically used in mining, tunnelling and rock slope stabilization applications to improve flexural toughness, impact resistance and ductility
- Monofilament Macro-Synthetic Fibers - A new generation of fibers that provide the same hardened properties (flexural toughness and energy absorption) as steel fibers.

Quality Assurance (QA) Quality Control (QC)

- Shotcrete acceptance/rejection criteria
 - Plastic shotcrete
 - Age, temperature and setting time
 - Sags, sloughing, tears
 - Reinforcing encapsulation
 - Line, grade and cover
 - Finish and tolerance

Quality Assurance (QA) Quality Control (QC)

- Shotcrete acceptance/rejection criteria
 - Hardened shotcrete
 - Compressive strength (cores from panels)
 - Flexural strength (beams)
 - Toughness (circular panels)
 - Permeability (boiled absorption)

Application of Shotcrete

Guidelines in ACI 506R-05 “Guide to Shotcrete”



Good Shooting Practices

Shooting edges of the repair area and working towards the center, to prevent trapping rebound in the corners.



Good Shooting Practices

The shotcrete on this pier was gunned in place in one day. The shotcrete easily conforms to the round contour of the pier where forming would have been extremely expensive.



Finishing Shotcrete

- Finishing operations are usually done because of Aesthetics or Technical reasons:
 - Smooth surface: flow characteristics, etc
 - Rough surface: bond of further layer, etc
- Finishing operations have an impact on cost depending on the requested flatness and smoothness

Types of Shotcrete Finish

Examples

- Natural or gun finish
- Cut
- Broom or brush finish
- Sponge finish
- Floated or troweled
- Carved
- Textured
- Exposed aggregate
- Painted & Stained



Typical Float Finish



american
shotcrete
association

ASCA

Types of Finish



Screeded finish

Float finish

Sponge Finish



Completed Shotcrete Piers




Match existing contours
without expensive formwork



Curing Shotcrete

- Curing is required to fully hydrate cement and increase strength
- Hydration will stop quickly if internal concrete moisture drops below 80%
- Curing ***MUST*** start immediately in hot, dry or windy conditions: use fogging/misting devices

Proper Curing Practices



Curing Compounds

- Alternative when wet curing is not practical
- Reduces evaporation, but does not compensate for moisture loss
- Curing compound must be removed before application of subsequent layers of shotcrete
- 2X the rate




Benefits of Pre-blended Materials

- Allows homogeneous blending of raw materials of varying densities (silica fume & cement)
- Improved distribution of fibers (when applicable)
- Improved air entrainment properties
 - *Air content, Air Void Distribution, Spacing Factor*



ACI Nozzleman Certification Program



**So what are you
still waiting for?**



**It's time to get your
nozzlemen trained
and certified!**

The American Shotcrete Association, in partnership with the American Concrete Institute, has developed a comprehensive program to upgrade the knowledge and skills of shotcrete nozzlemen and to facilitate ACI examination and certification. Provide your clients with the assurance that your nozzlemen have demonstrated that they have the capabilities to perform the job right—the first time!

To learn more or to schedule an ASA training session and an ACI Shotcrete Nozzlemen Certification examination, visit www.shotcrete.org or call (248) 848-3780.




Requirements for Nozzleman Certification

- Must incorporate ASA mandatory education
- Requires 500 hours of documented experience that can be verified by the examiner
- Written examination, Oral examination, practical examination (test panels are shot and core graded)
- ACI Nozzleman Certification application is processed by ASA

Note: upon passing, will be posted to ACI & ASA websites & receive complimentary 1-yr ASA membership

ACI Certification Panel



Use Qualified Contractors

It is the responsibility of the owner/specifier to ensure that the shotcrete contractor and his crew are qualified to properly complete the project.

This responsibility starts (but does not end) with nozzleman certification!

Before Issuing a Contract:

1. Ensure the contractor has a long and successful business history (check references)
2. Ensure the contractor has successful history on similar projects (check references)
3. Ask for work history of the contractor's key personnel (nozzlemen and supervisors)
4. Ensure the nozzleman possesses the experience and skill for the project
5. Ensure that all nozzlemen are currently certified for the method (dry and/or wet) and orientation (vertical and/or overhead) for which they will be shooting

www.ACIfcertification.org/verify

american
shotcrete
association

ASQ

Useful Tools and Resources

- www.shotcrete.org/buyersguide (source contractors, consultants and suppliers with related project experience)
www.ACIncertainment.org (for information on nozzlemen certification)
- ASA Staff – 248-848-3780 or info@shotcrete.org
- ACI Certification Staff – 248-848-3790 or john.nehasil@concrete.org

This concludes The American Institute of Architects
Continuing Education Systems Course

american
shotcrete
association



american
shotcrete
association



Abraham Lincoln Memorial Bridge Interstate 39 in LaSalle, Illinois



7,122 ft in length with 2 lanes
in each direction




86 piers approximately
70 ft. high above rivers, lakes,
wetlands & railroads


american
shotcrete
association

ASQ

**50 ft. by 6 ft. Platforms weighing
more than 6,000 lbs.**



Over 30,000 lbs. of reinforcement supplemented





**All shotcrete work completed by ACI
certified nozzlemen**

american
shotcrete
association

ASQ

Cured with wet cotton mats
for 7 days



15,000 CF of removal and replacement



Dan Ryan Expressway Chicago, Illinois

Elevated structure runs through the heart of the City of Chicago



One of the largest and busiest expressways



120 piers
approximately
60 ft. high above local
roads, businesses &
railways



60 ft. boom lifts
used to access
piers


american
shotcrete
association

ASCA

**Over 15,000 lbs. of reinforcement
supplemented**



All shotcrete work was done from the ground and pumped upward to the nozzle



Completed by ACI certified nozzlemen

**Cured with wet
cotton mats for 7
days**



use of shotcrete over form and pour was chosen for its advantages in scheduling and sustainability

american
shotcrete
association

ASCA

11,000 cubic feet
of removal and
replacement



The Noblestown Road Bridge



american
shotcrete
association

ASCA

The Deterioration of Piers



Pier hammerhead, the rusting reinforcing bars caused the entire underside of this pier hammerhead to delaminate and spall from the surface.



Drainage problems led to the corrosion of the reinforcing bars and the expanding rust scale caused the concrete to spall



The deterioration on this pier hammerhead vividly illustrates the urgency of this rehabilitation project



american
shotcrete
association



Preparation of Repair Areas

The repair areas were delineated, saw cuts were made and the deteriorated concrete was removed behind the first layer of reinforcing bars. The reinforcing bars were sandblasted to remove the scale, prior to the installation of the wire mesh.



Preparation of Repair Areas

The concrete was deteriorated from the reinforcing bars outwards, however on this pier even sound concrete was removed to allow the shotcrete to wrap around and encapsulate the reinforcing



Different Repairs on a Pier

Shotcrete repairs were specified in most areas but conventional form and pour repairs were required on this pier where the right side of this pier hammerhead is set up for forming operations.



The bridge was supported during removal and repair operations



Shotcrete allows easy overhead placement



american
shotcrete
association



In Place Shotcrete

This freshly gunned pier hammerhead shows the results that can be achieved when shotcrete is placed correctly with an experienced crew.



Eliminating Difficult Forming Work

The shotcrete easily conformed to the shape of the round piers on this freshly gunned pier, providing an excellent result.



Prepackaged Materials



Prepackaged materials were used. To the left the shotcrete material is being pre-dampened prior to gunning and to the right are the 3000 lb sacks and holding hopper.

Supporting the bridge during concrete removal and shotcrete

During construction operations the bridge was supported. Traffic was diverted to the two east or west bound lanes and only one side of a pier could be removed and placed at a time.



Completed Shotcrete Piers



Completed Shotcrete Piers



Completed Shotcrete Repairs



Tunnel Project

Project Name:

Liberty Tunnels Phase 2

Project Location:

Pittsburgh, PA

Shotcrete Contractor:

Mosites Construction Co.

General Contractor:

Mosites Construction Co.

Architect/Engineer:

Parsons Brinkerhoff

Material

Supplier/Manufacturers:

The Quikrete Companies*

Project Owner:

Pennsylvania Department
of Transportation

* Corporate Member of the American
Shotcrete Association



american
shotcrete
association

ASQA

Tunnel Project



Where necessary,
additional reinforcement
was installed.

Prior to material installation
the substrate was prepared
using hydro-demolition.



Tunnel Project



The 3000 lb bulk bags were predampened as a part of the installation process.

Shotcrete being applied vertically by an ACI certified nozzleman.



Tunnel Project



Shotcrete being applied overhead by an ACI certified nozzleman.

Finished wall with a white to clear curing agent.



Tunnel Project



Finished patch on ceiling with white to clear curing agent.

Prepared substrate ready for application of flashcoat.



american
shotcrete
association

ASCA

Tunnel Project



Finished tunnel







association



























