

By Standard Number / 1910.95 App I - Definitions

- **Part Number:** 1910
 - **Part Number Title:** Occupational Safety and Health Standards
 - **Subpart:** 1910 Subpart G
 - **Subpart Title:** Occupational Health and Environmental Control
 - **Standard Number:** 1910.95 App I
 - **Title:** Definitions
 - **GPO Source:** e-CFR
-

These definitions apply to the following terms as used in paragraphs (c) through (n) of 29 CFR 1910.95.

Action level - An 8-hour time-weighted average of 85 decibels measured on the A-scale, slow response, or equivalently, a dose of fifty percent.

Audiogram - A chart, graph, or table resulting from an audiometric test showing an individual's hearing threshold levels as a function of frequency.

Audiologist - A professional, specializing in the study and rehabilitation of hearing, who is certified by the American Speech-Language-Hearing Association or licensed by a state board of examiners.

Baseline audiogram - The audiogram against which future audiograms are compared.

Criterion sound level - A sound level of 90 decibels.

Decibel (dB) - Unit of measurement of sound level.

Hertz (Hz) - Unit of measurement of frequency, numerically equal to cycles per second.

Medical pathology - A disorder or disease. For purposes of this regulation, a condition or disease affecting the ear, which should be treated by a physician specialist.

Noise dose - The ratio, expressed as a percentage, of (1) the time integral, over a stated time or event, of the 0.6 power of the measured SLOW exponential time-averaged, squared A-weighted sound pressure and (2) the product of the criterion duration (8 hours) and the 0.6 power of the squared sound pressure corresponding to the criterion sound level (90 dB).

Noise dosimeter - An instrument that integrates a function of sound pressure over a period of time in such a manner that it directly indicates a noise dose.

Otolaryngologist - A physician specializing in diagnosis and treatment of disorders of the ear, nose and throat.

Representative exposure - Measurements of an employee's noise dose or 8-hour time-weighted average sound level that the employers deem to be representative of the exposures of other employees in the workplace.

Sound level - Ten times the common logarithm of the ratio of the square of the measured A-weighted sound pressure to the square of the standard reference pressure of 20 micropascals. Unit: decibels (dB). For use with this regulation, SLOW time response, in accordance with ANSI S1.4-1971 (R1976), is required.

Sound level meter - An instrument for the measurement of sound level.

Time-weighted average sound level - That sound level, which if constant over an 8-hour exposure, would result in the same noise dose as is measured.

[39 FR 23502, June 27, 1974, as amended at 46 FR 4161, Jan. 16, 1981; 46 FR 62845, Dec. 29, 1981; 48 FR 9776, Mar. 8, 1983; 48 FR 29687, June 28, 1983; 54 FR 24333, June 7, 1989; 61 FR 5507, Feb. 13, 1996; 61 FR 9227, March 7, 1996]

UNITED STATES DEPARTMENT OF LABOR

Occupational Safety & Health Administration

200 Constitution Ave NW

Washington, DC 20210

☎ 800-321-6742 (OSHA)

TTY

www.OSHA.gov

FEDERAL GOVERNMENT

White House

Severe Storm and Flood Recovery
Assistance

Disaster Recovery Assistance

DisasterAssistance.gov

USA.gov

No Fear Act Data

U.S. Office of Special Counsel

OCCUPATIONAL SAFETY & HEALTH

Frequently Asked
Questions

A - Z Index

Freedom of Information
Act (FOIA)

Read The OSHA
Newsletter

Subscribe to the OSHA
Newsletter

OSHA Publications

Office of Inspector
General

ABOUT THIS SITE

[Freedom of Information Act \(FOIA\)](#)

[Privacy & Security Statement](#)

[Disclaimers](#)

[Important Web Site Notices](#)

[Plug-ins Used by DOL](#)

[Accessibility Statement](#)