

# Timber Bridges in the U.S – Past, Present and Future

---

Michael Ritter, Assistant Director  
USDA Forest Service, Forest Products Laboratory  
Madison, Wisconsin



# Presentation Overview

- The Forest Resource
- Evolution of Materials and Designs
- The Timber Bridge Initiative
- Where We are Today
- An Opinion on the Future



# The Forest Resource

*It's all about the resource*






# *The Forest Resource*





# *The Forest Resource*





# *The Forest Resource*






# *The Forest Resource*



# *The Forest Resource*





# The Forest Resource

H.H.

U. S. DEPARTMENT OF AGRICULTURE,  
DIVISION OF FORESTRY,  
WASHINGTON, D. C.

GIFFORD PINCHOT, FORESTER.  
HENRY S. GRAVES, SUPT. OF WORKING PLANS.  
J. W. TOUMEY, SUPT. OF TREE PLANTING.  
GEO. B. SUDWORTH, DENDROLOGIST.  
OTTO J. J. LUEBKERT, HEAD CLERK.

February 2, 1900.

Mr. John Muir,  
Martinez, Calif.

Dear Mr. Muir:

Many thanks for your telegram, which gives me exactly the information I was after. We are going to try to interest Congress in the preservation of the Calaveras Groves. I will keep you posted from time to time as the matter progresses.

Very sincerely yours,

*Gifford Pinchot*

Forester.

*What is being done in California to save these trees?*





# *The Forest Resource*





# *The Forest Resource*

1910 - 1931





# *The Forest Resource*





# *The Forest Resource*





# *The Forest Resource*





# *The Forest Resource*





# *The Forest Resource*





# *The Forest Resource*



Fire readiness and suppression has gone from 20% of the FS budget in 2001 (approximately \$1 billion) to over 60% (approximately 3\$ billion) in 2014. It is not uncommon to spend \$1 million per hour fighting fires.





# *The Forest Resource*





# *The Forest Resource*





# Material and Design Evolution

*The last 150 years*





# *Material and Design Evolution*





# *Material and Design Evolution*



*208' high x 843' long*




# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*






# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*






# *Material and Design Evolution*






# *Material and Design Evolution*







# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*



1948




# *Material and Design Evolution*






# *Material and Design Evolution*






# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*





# *Material and Design Evolution*



Press-Lam PLV 1979



# *Material and Design Evolution*



*Open Deck Design*





# *Material and Design Evolution*



*Ballast Deck Design*





# Timber Bridge Initiative

1989 – 2004

*We must understand the past to  
grow in the future*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*






# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*





# *Timber Bridge Initiative*



**ALAMCO**  
WOOD PRODUCTS, LLC






# Where We are Today

*What is the situation, what are the opportunities and challenges?*





# *Annual Growth and Removal*







# *National Bridge Inventory – 12/2012*

- 607,380 bridges (over 20' span)
- 22,724 bridges are wood bridges
- 151,497 bridges are deficient
  - 66,749 bridges are “Structurally Deficient”
  - 84,748 bridges are “Functionally Obsolete”
- Pennsylvania, Oklahoma and Iowa have the highest percentage of deficient bridges





# Bridge Replacement is a Critical Need



## Transportation for America





# *Where We are Today*


## Challenge: Longevity Misconception






# *Where We are Today*

## Challenge: Longevity Misconception



1966

2010





# *Where We are Today*

Challenge: Strength Misconception





# *Where We are Today*

## Challenge: Strength Misconception





# *Where We are Today*

Challenge: Strength Misconception





# *Where We are Today*

## Challenge: Durability Misconception





# *Where We are Today*

## Challenge: Durability Misconception





# *Where We are Today*

## Challenge: Durability Misconception





# Where We are Today

## Challenge: Durability Misconception

### Perception versus Reality: An Analysis of Timber Bridge Performance in the United States.

Robert L. Smith, Virginia Tech  
Kim Stanfill-McMillan, Forest Products Laboratory, USDA Forest Service

#### Abstract

Bridge material selection is one of the most difficult decisions an engineer has to make. Many factors and individuals are often involved in choosing the proper bridge material for a given site and location. Not only physical factors such as strength or lifespan of material, but also site specific factors like roadway alignment and traffic count play important roles in material selection. It is not uncommon for state Department of Transportation engineers, private consulting engineers, and local highway officials all play roles in the material selection process. Each individual may have his/her own perception of bridge materials based upon past experience and education. And little is known how these perceptions influence the choice of materials. In this study perceptions of engineers and highway officials toward timber as a bridge material were compared to the actual performance of timber as reported in the National Bridge Inventory. To accomplish this case studies were conducted in four selected states. Highway officials and engineers in Mississippi, Virginia, Washington, and Wisconsin were surveyed by mail and personally interviewed to capture their perceptions toward timber as it compared to other major bridge materials (prestressed concrete, steel, and reinforced concrete). This information was compared with the actual performance data obtained from the National Bridge Inventory. The results indicate that there is a strong correlation between highway officials' perceptions towards bridge materials and the reported performance of these materials.

Keywords: Perceptions, National Bridge Inventory, timber, steel, concrete, performance.

#### Introduction

The need for bridge replacement has been well documented (Brunguber et al. 1987, Cheney 1986, USDA 1989). Over 40% of our Nation's bridges are in need of repair or replacement. According to the FHWA (1992) four major structural materials make up over 98% of all bridges in the United States. These include prestressed concrete (15%), steel (36%), reinforced concrete (40%), and timber (8%). However, since 1982 over seventy percent of the replacement bridges have been prestressed or reinforced concrete, while timber and steel were used in less than thirty percent of replacement structures. This suggests that perceptions toward prestressed and reinforced concrete by highway officials are better than that of competing materials.

The United States has more than 3.9 million miles of roadway and 575,000 bridges. In 1967, in response to the collapse of the Silver River bridge over the Ohio River, Congress mandated the implementation of National bridge inspection standards. The individual bridge inspection records constitute the National Bridge Inventory (NBI). The purpose of the NBI is to provide a uniform base of bridge information that can be used to identify those bridges that are most in need of repair and to serve as a basis for allocating Federal Highway Administration (FHWA) funding for bridge replacement or rehabilitation. The NBI is administered by the FHWA in Washington, D.C. Data are updated continuously based on the latest bridge inspection, which are usually completed on a two year cycle.





# *Where We are Today*



## Challenge: Fire Performance





# *Where We are Today*

## Challenge: Fire Performance





# *Where We are Today*

## Challenge: Fire Performance





# *Where We are Today*

## Challenge: Fire Performance





# *Where We are Today*

## Challenge: Engineering Education



The National Council of Structural Engineers  
Associations recommends one course in Timber  
Behavior and Design





# *Where We are Today*

## Challenge: Engineering Education





# *Where We are Today*

## Challenge: Contractor Education





# *Where We are Today*

## Challenge: Contractor Education






# *Where We are Today*


## Challenge: Contractor Education

Glued Laminated Timber




Longitudinal Decks

Glued Laminated Timber



Stringer Bridges

Glued Laminated Timber



Stress-Lam Decks



# *Where We are Today*

## Challenge: Design Awareness





# *Where We are Today*

## Challenge: Design Awareness





# *Where We are Today*

## Challenge: Design Awareness





# Where We are Today

## Economics



United States  
Department of  
Agriculture  
**Forest Service**

Forest  
Products  
Laboratory  
National Wood  
in Transportation  
Information  
Center


Research  
Paper  
FPL-RP-593



In cooperation  
with the  
United States  
Department of  
Transportation  
Federal  
Highway  
Administration



## Timber Bridge Economics



### National Cost Study of Timber Bridges

Glade M. Sowards, John Z. Wang, Blair Orr, Michigan Technological University

Kim Stanfill-McMillan, Forest Products Laboratory, USDA Forest Service

#### Abstract

A study is underway to determine the initial cost of timber bridges compared to those of steel, concrete, and prestressed concrete bridges. This report discusses the early results of the timber bridge portion of the data set. To this end, timber bridge owners, as identified in the June 1994 National Bridge Inventory (NBI), were sent a specially designed questionnaire to survey cost information on timber bridges under their ownership. In order to establish a comparative basis, timber bridges were selected under the requirements that they be built no earlier than 1980 and be load rated according to American Association of State Highway and Transportation Officials (AASHTO) specifications. No private or government demonstration bridges were included in this study. Given these requirements, 1604 timber bridges were identified as survey bridges. This paper summarizes the analysis of data collected on the cost of timber bridge superstructures throughout the country. The results of such analysis suggest that unit costs were highest for both the longest and shortest bridges considered and tend to increase with higher load ratings. Additionally, it was noted that questionnaire responses were lower than expected for shorter, narrower bridges that were designed to carry lighter loads.

Keywords: Timberbridge(s) superstructure cost.

#### Purpose And Background

According to Smith and Bush (1994), there are approximately 200,000 deficient bridges throughout the country with a projected replacement cost of \$84 billion. As Wolchuk (1988) indicates, concrete decks account "for about two-thirds of the deficiency cases." In the face of such staggering

figures, there has been a renewed interest in the prospect of timber bridge utilization.

Throughout much of the 19th century, timber structures accounted for the majority of the bridges and railroad trestles in the United States. These were simple structures constructed of sawn lumber. Many timber bridges of the period even lacked preservative treatments that would allow them to withstand exposure to moisture and decay. Additionally, the older timber bridges were often crudely designed with little or no input by engineers. For example, it was not until 1840 that a complete stress analysis of a timber bridge design was included with the bridge designer's patent. In the 20th century, timber bridges were first replaced by steel. Steel competed with timber as a bridge construction material on a first-cost basis by 1910 and came to dominate the bridge market by 1930 (Ritter 1990).

The failure of older, primitive timber bridges and their eventual replacement by newer steel and, later, concrete designs is the likely source of a general perception held by some today that timber bridges are of inferior quality. Over time, however, the limitations of steel, concrete, and prestressed concrete have become apparent and range from susceptibility to corrosion to costly maintenance and replacement.

Beginning in the mid-1940s engineers began to reconsider timber for bridge construction. The development of such techniques as glue- and, later, stress- lamination demonstrated the strength of timber as a construction material and led to a renewed interest in timber bridge utilization (Ritter 1990). The rationale for this interest is three-fold. First, timber offers a potentially low-cost





# *Where We are Today*

Opportunity: Versatility





# *Where We are Today*

Opportunity: Versatility





# *Where We are Today*

## Opportunity: Versatility





# *Where We are Today*

## Opportunity: Versatility





# *Where We are Today*

## Opportunity: Versatility



 WESTERN  
WOOD  
STRUCTURES





# *Where We are Today*

## Opportunity: Versatility



 WESTERN  
WOOD  
STRUCTURES





# Opinion on the Future





# *The Future*

## New Materials



1988 in Austria





# *The Future*

## New Materials





# *The Future*

## Composite Bridges






# *The Future*

## Smart Bridges and Remote Sensing





# *The Future* Fireproof Coatings






# *The Future*

## Nanotechnology

Nanotechnology is the understanding and control of matter at dimensions of 1 to 100 nanometers, where unique phenomena allow us to make new materials and devices with novel applications




1 nanometer = 1 billionth of a meter



# *The Future*

## Nanotechnology




Nanoparticles of metals commonly used to preserve wood demonstrate unique properties compared to larger particles of the same material, including increased leach resistance, photostability and termite inhibition



# *The Future* Nanotechnology

USDA  
United States  
Department of  
Agriculture  
Forest Service  
Forest  
Products  
Laboratory  
General  
Technical  
Report  
FPL-GTR-210





## Literature Review and Assessment of Nanotechnology for Sensing of Timber Transportation Structures Final Report

Terry Wipf  
Brent M. Phares  
Michael Ritter






# *The Future* Adhesives





# *The Future*

## Sustainability and Green Building








# *The Future*

## Sustainability and Green Building



Center for Environmental Excellence by AASHTO


One Stop Source of Environmental Information for Transportation Professionals





# *The Future*

## Sustainability and Green Building





# The Future

## Sustainability and Green Building

### Environmental Product Declaration

#### Typical Western Red Cedar Bevel Siding

"1/2 x 6" Clear Grade, Painted

Type III environmental declaration developed according to ISO 21930 and 14025 for average cedar siding products manufactured by the members of the Western Red Cedar Lumber Association.


Issued April 2011  
Valid until April 2016





# *The Future*

## Research and Development





# *The Future*

## Education and Technology Transfer

**NATIONAL  
CENTER  
FOR WOOD  
TRANSPORTATION  
STRUCTURES**  
[www.woodcenter.org](http://www.woodcenter.org)



# WoodWorks





# Conclusions

- Timber bridges are an excellent value-added option for a “growing” wood resource.
- Bridge replacement needs increase annually, especially on secondary road systems.
- There are numerous proven timber bridge designs.
- Acceptance of timber bridges can be further increased through education and technology transfer.
- Research must continue to develop and demonstrate new bridge systems, materials and technologies.
- The future is potentially bright!





# Thank You

