
## Subgrades & Subbases: Iowa DOT Research and Next Steps







#### **Outline**

- Overview of challenge facing the DOT
- Background & results of research projects
  - STIC project
  - AID project
- Overview of DOT Implementation Plan
- Closing comments and questions

## Challenge facing the DOT

- The primary system includes 24,534 lane miles of pavement.
- Value to replace is over \$14 billion
- Half of the system's original pavement is more than 55 years old.
- 29% (6,792 miles) is 70+ years old

### Challenge facing the DOT


- Current situation with funding.
- Need to extend pavement life.
- How?
  - Improve material performance
  - Improve foundations
  - Continually improve construction quality

### **Research Projects**


- 2017 & 2018, STIC (State Transportation Innovation Council) Incentive Program: \$100k
- 2019 & 2020, AID (Accelerated Innovation Deployment) Demonstration Program: \$700k




## **Roller Mapping of Modulus**



# Different typical foundation layer support conditions were evaluated at the 10 project sites.



## Modulus is the most critical foundation input parameter in pavement design, and field verification of this value is important!



#### **KEY Outcomes of this project are:**

- ✓ M<sub>r</sub> values are variable across the state and within each project site. C<sub>v</sub> between 5% and 80% at each site.
- √ k-values across the site varied between 35 and 300 pci. 11 out of 14 tests showed < 150 pci.
  </p>
- ✓ Sites with 2 ft of special backfill material provided higher Mr values than other sites.
- ✓ Typical values provided in the ME Design Guide based on soil classification are not reliable.

#### **KEY Outcomes of this project are:**

- K values over granular or modified were lower than those directly on underlying subgrade material.
- ✓  $\delta_p$  from static PLT varied between 0.05 and 0.4 in., with 11 out of the 14 tests > 0.05 in. critical limit.
- ✓ FE analysis showed that the two most important factors to reduce bending stresses in the pavement layer are pavement thickness and  $\delta_{\rm p}$ .

### **AID Project Objectives**

- Continuation of APLT testing and incorporation of VIC technology
- Understand results obtained from current requirements
  - Measure modulus of foundation layers that are built with current specification requirements
- Shadow test with VIC and APLT technology

## **AID Project Objectives, Cont.**

 Develop e-Construction system that allows near real time use of data

- Develop Implementation Plan
  - Identify improvements to current specifications (materials and construction requirements)
  - Identify changes to current pavement design procedures



#### **AID TWG Members**

#### **Iowa DOT**

- Newman Abuissa
- Ben Behnami
- Chris Brakke
- Vanessa Goetz
- John Hart
- **David Heer**
- Dean Herbst
- Hugh Holak
- Stephen Megivern
- Kevin Merryman
- **Brian Moore**
- Wes Musgrove
- Jeffrey Schmitt
- Melissa Serio
- **Dustin Skogerboe**

#### **Industry Stakeholders**



:JETERSON

**-**ONTRACTORS

- Dan King (ICPA)
- Ryan Kipp (CJ Moyna)
- Adam Kos (CJ Moyna)
- Brian Manatt (Manatts)
- Greg Mulder (ICPA)
- Ron Otto (AGC Iowa)
- Cork Peterson (PCI US) Scott Dockstader (APAI)
- Steve Streb (Streb Construction)
- Tim Tometich (Manatts)

#### **FHWA**

- Micah Loesch
- Lisa McDaniel



## **MICHIGAN STATE**

#### **Academia**

Prof. Bora Cetin (Michigan State University)

#### **Ingios**


- Tom Cackler
- Bruce Cunningham
- Brendan Fitzpatrick
- Kera Gieselman
- LaDon Jones
- Craig Swanson
- Colby VanNimwegen
- Pavana Vennapusa
- **David White**











### 2019-2020 Scope for Mapping Verification

#### 2020:

No.	of Projects S	ites: 9	)
	0 1 1 0 1 0 0 0 0		

No. of Maps Performed: 134

No. of APLT Performed: 78

#### 2019:

•	No. of	Projects	Sites:	6
---	--------	----------	--------	---


No. of Maps Performed: 38

• No. of APLT Performed: 59


## E-construction Data Flow & Processing








# COMP-Score calibration of k-values on-site provides high confidence in the modulus mapping outputs.




#### Blackhawk County, US20 Project (08/27/2019)






#### Hamilton County, I35/Hwy175 (09/03/2019)



#### **Jasper County, I-80 (06/18/2020)**




#### **Jasper County, I-80 (06/18/2020)**




### Blackhawk County, US20 (09/05/2019) - Modified Subbase

**Delta k-value Map** 




#### Blackhawk County, US20 (09/05/2019) - Modified Subbase

#### **Delta Design Life Map 1**




#### Blackhawk County, US20 (09/05/2019) - Modified Subbase


#### **Delta Design Life Map 2**




#### Des Moines County, US61 (10/23/2019 – FALL) Select Subgrade



#### Des Moines County, US61 (05/16/2020 – Spring) Select Subgrade








# How does current compaction specification on Granular Subbase affect Drainage Vs. Stiffness




US61, Des Moines County (06/16/2020) Granular Subbase – Crushed Limestone

# Summary of Vu Meter Test Results from multiple project sites



### Secondary Roads Evaluation using COMP-Score™ RT







## Mapping Length:

21 miles




## Mapping Duration:

6 hours




Number of Data Points: 38,729

Analysis underway to assess % of roadway needing repair, with options for repair (remove/replace or thicker gravel layer or stabilization options)



Reference Target Composite Modulus Value [9,000 psi]

# Compaction reports are a key component of what COMP-Score™ CONNECT delivers.



# Compaction reports are a key component of what COMP-Score™ CONNECT delivers.

<b>COMP-Score™ CONNECT RE</b>					ORT		
Project:	NHSX-020-6(71)3H-07	Date and Time:	8/27/19 4:35 PM	Mean:	107.7	Compaction Quality Index:	30.3
Map ID:	INGIOS_DEMO-0_CS562008_2019_08_27_113527	Mapping Duration (hrs):	0.42	Standard Deviation:	32.8	Calibration Index:	0.36
Location:	Black Hawk US20	No. of Measurements:	2967	Coeff. of Variation (%):	30	Target Value:	150.0
Operator:	Ingios	Data Parameter:	k-value	Passing Target (%):	16	Review Required:	YES
Machine ID:	Ingios_FCS00210	Measurement Unit:	psi/inch	Report Status:	REVIEW PEND	ING	

#### QUALITY ANALYSIS SUMMARY

k-value

Quality analysis metrics give the viewer a quick glance at how the mapping performed against established targets.

QUALITY VALUE	CRITERIA		
30.3	CQI >= [95]		
15.5	[80%] of [k-Value] MVs >= [k-value_TV]		
30	COV <= [30]		
46	% i-Score Blob Area >= 200 ft <sup>2</sup>		
	[80%] of [w%] >= w%_TV		

Compaction Quality Index(CQI): Relative compaction quality index based on the percentage of the geospatial area that meets the minimum target values and accounts for the uniformity of compaction. The default minimum target CQI is 95 % using a uniformity weight factor of 50 %.

Percent Passing Target Values: Number of geospatial grid points from the output that meet or exceed the target value for the selected material. The default target % \_Passing TV 80 %.

Coefficient of Variation (COV): Calculated from the ratio of the standard deviation to the mean based on the MVs reported at each grid point of the mapping area. The default target COV is 30%. Description of COV ranges: 20% = Low Variability; 20 to 40% = Moderate Variability; and greater than 40% = High Variability.

i-Score Blob (%): Represents the percentage of the area within the map area that has been identified from i-Score Blob Analysis as a prioritized contiguous area that is > = 200 sq. ft, with MVs < target values. Description of i-Score Blob: 0% = No rework needed; 0 to 20% = Some rework needed; 20 to 30% = Moderate rework needed; > 30% = Signficant rework needed.

#### Pilot Projects - 2021

- Boone County, IA 17
  - Grading
  - Approx. 0.5 miles N. of US 30 north and east approx. 3 miles
  - January 20, 2021 letting
- Black Hawk County, US 20
  - PCC Pavement Replace
  - US 63 to IA 21 in Waterloo (EB / WB)
  - February 16, 2021 letting

### **Pilot Projects - 2021**

- Special Provision: Modulus Verification Using Roller Mapping of Pavement Foundation Layers
  - Equipment Requirements
  - Training Requirements
  - Mapping Requirements
  - MOM & BOP

#### **Overview of Implementation Plan**

- 5 Year Plan (2021 2025) to transition from pilot projects to full implementation
- Plan is to have each RCE Office get project experience
- DOT considering having Ingios map completed grading projects in 2021 to support development of paving plans.
- Potential for county applications developed parallel with DOT implementation

#### **Overview of Implementation Plan**

#### **Anticipated DOT Project Applications**

- 2021 2 projects
- 2022 5 projects
- 2023 ~10 projects
- 2024 ~20 projects
- 2025 Statewide implementation as standard

#### **Overview of Implementation Plan**

- Develop SPs for use in future years
- Develop training program to possibly integrate into DOT existing web-based curriculum
- Develop LCCA models
- Identify other DOTs interested in technology partnership

## **Closing Comments**

- Additional questions/discussion?
- Thank you for attending!

Melissa Serio
Earthwork Field Engineer
Construction & Materials Bureau, Iowa DOT

Melissa.serio@iowadot.us

Ph. 515/239-1280